

## Universal Fire Collar

Multicollar Slim is a 30 mm-high universal fire collar that consists of a stainless steel band made of 174 segments and a high-quality inlay on a graphite basis. In order to achieve the desired pipe diameter, the links can easily be separated. In the event of fire, the Multicollar Slim starts foaming and creates a fire-resistant seal to adjacent rooms. In combination with the Multisealant A sealant, it is also possible to achieve a smoke-proof finish. This fire collar has been extensively tested in Europe in accordance with EN 1366-3. The Multicollar Slim fire collar is a single product for all applications. Thanks to the Multiclips and Multiscrews included in the box, one person can easily install it. Multicollar Slim forms part of the Mulcol® Penetration Seal System.

### Type of penetrations

- ✓ Standard plastic pipes Ø315mm - PVC-U, PVC-C, PP, PE-HD, ABS, SAN+PVC
- ✓ Sound-proofing plastic pipes - REHAU Raupanio plus, Geberit Silent-20dB, Wavin SiTech+, Wavin AS, Blue Power, POLO-KAL 3S
- ✓ Aluminium composite pipes such as: PE-Xb, PE-Xc, PE-RT, Henco, Uponor, Wavin Tigris, Geberit Mepla, REHAU Rautitan
- ✓ Fibre composite pipes such as: PP-R, PP-B, PP-RCT, Aquatherm, Climatec, Aquatechnik
- ✓ Air-conditioning pipes such as : Wicu Flex
- ✓ Copper and steel pipes
- ✓ Electric cables and cable bundles
- ✓ Cable pipes with and without electric cables
- ✓ Aluminium flue gas discharge pipes
- ✓ Concentric flue gas discharge pipes steel/PP

### Tested configurations

- ✓ Pipes in combination with steel pipe support shells
- ✓ Angled pipes
- ✓ Pipes with a zero distance room walls and floors, U-shaped collar
- ✓ Pipes under a 45° angle
- ✓ Pipes tested with tuck-in, electric welding and glue sleeves
- ✓ Pipes with 87°/90° and 2x 45° corner pieces
- ✓ Multiple pipe solutions
- ✓ Pipes with or without insulation



## Advantages

- Fire resistance  $\leq$  120 minutes
- Tested up to  $\varnothing$  315 mm
- CE-certified
- Environmentally and user-friendly
- Easy to install
- One product for all applications
- One fixing medium for all structures
- Can be used anywhere thanks to its 30-mm height
- Also tested for non-standard applications
- User manual and all fasteners in one
- Damp, fungi and bacteria-resistant
- Halogen-free
- Working life of 30 years

## Applications

- Rigid floors and walls
- Flexible walls
- Shaft walls
- Firestop Boards



## Technical data

### Colour stainless steel band + inlay

**Application temperature** +5 °C to +50 °C

**Temperature resistance** -20 °C to +80 °C

**Reaction to fire** Class E in accordance with EN 13501-1

## Packaging

	Dimensions	Box	Outer box	Pallet	Article number
Roll (174 segments)	2610 x 30 x 12 mm	1 piece	8 pieces	384 pieces	206001174

### Accessories (included)

- ✓ 20 pieces of Multiclips, 30 mm
- ✓ 20 pieces of Multiscrews 7,5 x 40 mm
- ✓ 1 piece of Multibit T30
- ✓ 6 pieces of Conformity Statement

## Technical documents available

- ✓ Product Data Sheet (PDS)
- ✓ Technical Data Sheet (TDS)
- ✓ Safety Data Sheet (SDS)
- ✓ Installation Manual
- ✓ EC certificate

## Approvals

- ✓ Tested in accordance with EN 1366-3
- ✓ Classification in accordance with EN 13501-2
- ✓ Certified in accordance with EAD 350454-00-1104
- ✓ ETA report 17/0836
- ✓ Declaration of Performance (DoP)

## Consumption table for plastic pipes

				
Ømm	Segmenten	Multiclips	Multiclips large	Quantity/roll
16-40	15	2		11
50	17	2		10
56	18	2		9
63	19	2		9
75	22	2		7
80	23	2		7
90	25	2		6
100	27	3		6
110	29	3		6
125	32	3		5
140	36	3		4
160	40	4		4
200	48 (x2)	1	5	3(1,8)
250	59 (x2)	2	5	2(1.4)
315	72 (x2)	2	6	2(1.2)

